

Induktive Näherungsschalter, 2-Draht PNP/NPN

Inductive proximity switches, 2-wire PNP/NPN
 Finecourse di prossimità induttivi, 2-fili PNP/NPN

IP21-19 | IP21-9 | IP21-371

Varianten Versions / Tipi



IS5026




NBB3-V3-Z4




BI2-Q10S-AZ31X

Technische Daten Technical features / Dati tecnici

Endschalterfabrikat Producer switch / Marca finecorsa	IFM	P+F	Turck	
Endschaltertyp Switch type / Tipo finecorsa	IS5026 (PNP/NPN)	NBB3-V3-Z4 (PNP)	BI2-Q10S-AZ31X (PNP)	
Spannung Voltage / Tensione	5-36 V DC	5-60V DC	10-300V DC / 20-250V AC	
Stromaufnahme Maximum current / Massima corrente	0-200 mA	4-100 mA	100 mA	
Schaltfrequenz Frequency / Frequenza	2000 Hz	2000 Hz	50-60 Hz	
Anzeige Output indicator / Indicazione	LED gelb LED yellow / LED giallo	LED gelb LED yellow / LED giallo	LED rot LED red / LED rosso	
Schutzart Schalter (IP-Code) Enclosure switch / Protezione finec.	IP67	IP67	IP67	
Temperatur Temperature / Temperatura	-25°C ... +80°C	-25°C ... +70°C	-25°C ... +70°C	
Bestellnummer Ordering code / codice	IP2101-19	IP2101-9	IP2101-371	



IP2101-19 | IP2101-9 | IP2101-371



IP2101-19

Artikelnummer Code number / Numero codice

