

Induktive Näherungsschalter, 3-Draht PNP

Inductive proximity switches, 3-wire PNP
 Finecourse di prossimità induttivi, 3-fili PNP

Varianten Versions / Tipi



IS5001




NBB2-V3-E2



BI2-Q10S-AP6X

Technische Daten Technical features / Dati tecnici

Endschalterfabrikat Producer switch / Marca finecorsa	IFM	P+F	Turck	
Endschaltertyp Switch type / Tipo finecorsa	IS5001 (PNP)	NBB2-V3-E2 (PNP)	BI2-Q10S-AP6X (PNP)	
Spannung Voltage / Tensione	10-36 V DC	10-30V DC	10-30V DC	
Stromaufnahme Maximum current / Massima corrente	0-200 mA	100 mA	15-150 mA	
Schaltfrequenz Frequency / Frequenza	800 Hz	1000 Hz	2000 Hz	
Leerlaufstrom No-load suppl. current / Minima corr.	15 mA	15 mA	15 mA	
Anzeige Output indicator / Indicazione	LED gelb LED yellow / LED giallo	LED gelb LED yellow / LED giallo	LED gelb LED yellow / LED giallo	
Schutzart Schalter (IP-Code) Enclosure switch / Protezione finec.	IP67	IP67	IP67	
Temperatur Temperature / Temperatura	-20°C ... +80°C	-25°C ... +80°C	-25°C ... +70°C	
Bestellnummer Ordering code / codice	IP2101-7	IP2101	IP2101-78	



Artikelnummer Code number / Numero codice

